



Flexible sheet made of high quality PVC with viscose flocking
Suede-style finish
For interior use
Made-to-measure in desired shape and size

CHARACTERISTICS OF RANGE: 35 SUEDE-STYLE

| | | |
|----------------------------------|---|-------------------|
| WEIGHT PER UNIT AREA | 0,375 Kg/m ² (±10%) | EN 14716 |
| THICKNESS | 0,540 mm (±10%) | EN ISO 2286-3 |
| WIDTH OF STRIPS | 1,45 m stretched | |
| TENSILE STRENGTH* | lengthways > 12 Mpa | EN ISO 527-3 |
| | diagonally > 10 Mpa | EN ISO 527-3 |
| TENSILE STRENGTH* | lengthways > 140 % | EN ISO 527-3 |
| | widthways > 150 % | EN ISO 527-3 |
| REACTION TO FIRE | B-s3,d0 | EN 13501-1 |
| MAX. TEMPERATURE OF USE | 40°C | |
| MIN. TEMPERATURE OF USE | > -5°C | |
| MAXIMUM SURFACE AREA PER CEILING | 25 m ² | |
| DIMENSIONAL STABILITY | lengthways < 4,5 % | EN 14716 |
| | diagonally < 4.5 % | (10 min. at 70°C) |
| PRODUCT CERTIFICATION | CE | EN 14716 |
| PERMEABILITY TO WATER VAPOUR | < 50 g/m ² per 24h | EN 14716 |
| INDOOR AIR EMISSIONS** | A+ | |
| RECYCLABLE | totally | |
| STORAGE | Indoors, at room temperature, out of direct sunlight | |
| CLEANING | Suede-style ceilings are not washable. Satisfactory results have been obtained using a mild stain remover applied using absorbent cotton. | |



* In normal conditions: 23°C (± 1°C), relative humidity of 50%.

** Defined by decree of 19 April 2011 published in the Official Journal of the French Republic.

No known dermatological and allergic reactions, or sensitivity or irritation.

The residual vinyl chloride content is below 1 ppm.

The information we provide concerning this product is based on our current knowledge and as manufacturer we cannot provide any guarantee and accept no liability for factors beyond our control or knowledge.